



EUROSPRAYER

Bituminous binder sprayer

ALL-ROADS SPRAYER : the machine that matches all your jobsites

- ◆ The EUROSPRAYER can carry out all types of spraying : Surface Dressing, tack coat and priming.
- ◆ This machine guarantees a precise application with its on-board computer which automatically controls the binder application rate.
- ◆ The characteristics that make this machine the number one choice are: its accuracy of application, its robustness and its simplicity of use. Designed with the user in mind, the EUROSPRAYER is a machine that can cope with extreme climatic and operating conditions.
- ◆ To guarantee the highest reliability, the EUROSPRAYER has been designed with a minimum of complex components, for minimum downtime on site and quick and easy access to the main controls.

BENEFITS:



SIMPLICITY

IN-CAB CONTROL

- ◆ Joystick control with ergonomic display
- ◆ Automatically controlled application rate
- ◆ Quick access to the different controls of the machine (front/rear)



ROBUSTNESS

COMPONENTS' PROTECTION

- ◆ Protection of the main elements: spraybar and control cabinet
- ◆ Components selected for their resistance and their simplicity of repair
- ◆ Resistance to the hazards of demanding jobsites.



QUALITY

ACCURACY

- ◆ Spraybar's height adjustment from the cab
- ◆ Individual nozzle settings from the cab with automatic dosage control
- ◆ Quick heating system

MAIN OPTIONS

Automatic burner: A combistat allows the desired binder temperature to be set and the burner to be switched on and off automatically.

This ensures that the binder is always at the desired temperature.

In addition, the electronic ignition of the burner provides safety and comfort of use.

Telescopic spraybar: With a width of 4.80 m, the telescopic spraybar allows to cover a larger working width than with a knee spraybar. It allows to deploy only the necessary width, according to the site constraints, which offers an increased maneuverability.

Printer: This function allows you to monitor the jobsite and control the quantities applied with your sprayer.

TECHNICAL SPECIFICATIONS

Type of binder	All types of bituminous binders
Tank capacity	7,000 L 10,000 L 13,000 L 16,000 L
Insulation	100 mm Duralinox cover
Type of heating	Direct with manual or automatic burner
Dosing range	From 0.1 to 2 kg/m ² .
Spraybar	4,20 m (knee-joint) to 4,80 m (telescopic)
Handlance	5 m
Control	In cab - joystick with screen and automatic dosage control

